

# Cleaning LvL ONE<sup>®</sup>, Polished and Brushed wheels



1.



Rinse the wheel with water to prevent scratching and erosion; preferably with a high pressure cleaner.

2.



Pour a quantity of ALclean into a bucket and dilute with 1, 2 or 3 parts of water.

3.

- 1. =
- 2. =
- 3. =
- 4. =

Recommended quantities:

- 1. for difficult spots
- 2. for medium pollution
- 3. for regular use
- 4. for frequent use

4.



Gently brush ALclean onto the wheel.

5.



Rinse with clean water. Repeat these steps if needed.

6.



Dry the wheel.

## LvL ONE<sup>®</sup> and Polished wheels

7.




Continue by applying a small amount of ALpolish.

8.



Spread it evenly over the wheel using a moist cloth and polish the wheel.



Repeat steps 7 and 8 section by section to prevent the polish from drying out.

## Cleaning Products for Alcoa<sup>®</sup> Wheels

### ALclean

- Removes oxidation, disk brake dust, salt spray and road grime
- Use for Brushed, Mirror Polished and LvL ONE<sup>®</sup> finishes

### ALpolish

- Restore and maintain the shine of Mirror Polished, LvL ONE<sup>®</sup> Alcoa<sup>®</sup> Wheels
- Use after ALclean

### ALbrush2

- A premium quality brush with a rubber edge to protect wheels from getting damaged during cleaning



For additional information on cleaning and maintenance see section 'Care and Maintenance' of the Service Manual for Alcoa<sup>®</sup> Wheels.

Here you can buy

